



**Environmental Programs**  
P.O. Box 1663, MS M991  
Los Alamos, New Mexico 87545  
(505) 606-2337/FAX (505) 665-1812



**National Nuclear Security Administration**  
Los Alamos Site Office, MS A316  
Environmental Restoration Program  
Los Alamos, New Mexico 87544  
(505) 667-4255/FAX (505) 606-2132

*Date:* December 5, 2007  
*Refer To:* EP2007-0756

James P. Bearzi, Bureau Chief  
Hazardous Waste Bureau  
New Mexico Environment Department  
2905 Rodeo Park Drive East, Building 1  
Santa Fe, NM 87505-6303

**Subject: Recommendations for Removal of Mortandad Canyon Permeable Reactive Barrier**

Dear Mr. Bearzi:

This letter documents the Los Alamos National Laboratory's (the Laboratory's) recommended approach for removing the Mortandad Canyon permeable reactive barrier (PRB) as discussed with your staff on different occasions during the past three weeks. The PRB is being removed pursuant to the New Mexico Environment Department's (NMED's) requirement in the Approval with Direction of the Mortandad Canyon investigation report, dated February 23, 2007. Although not explicitly stated in the approval letter, a key objective of the removal project for both NMED and the Laboratory is to glean an understanding of the nature of compromised hydrologic and geochemical performance and the cause of subsidence of the surface overlying the barrier materials. In summary, the water-quality data obtained from the fourth in a series of cells containing reactive media are similar to the "influent" groundwater entering the first cell. It is hypothesized that the cause may be hydrologic bypass. The source of the subsidence is not known. The lessons learned from this project will be used in the application of PRB projects that the Laboratory may implement as part of future corrective measures such as those associated with the 260 site at Technical Area 16.

Following discussions with your staff, the Laboratory proposes that the objectives stated above can be met by removing only the reactive media and the separating septa within the primary structure. The approach will allow complete examination of the condition of the barrier structure to assess the integrity of its construction, especially as it pertains to potential hydrologic bypass of reactive media. As the various layers of material within the PRB are removed, detailed examination will also provide opportunities to assess the cause of the subsidence (e.g., compaction of reactive media vs. overlying fill material). Materials used to backfill the frame will be of sufficient hydraulic conductivity to ensure unrestricted flow of alluvial groundwater through this portion of the canyon.

This approach also significantly reduces (1) the safety issues if the frame is completely removed, (2) the footprint of the excavation and, therefore, disturbance of in-place alluvium, and (3) significant amounts of additional waste that may be generated.

If you have any questions, please contact Danny Katzman at (505) 667-6333 (katzman@lanl.gov) or Mat Johansen at (505) 665-5046 (mjohansen@doeal.gov).

Sincerely,



Susan G. Stiger, Associate Director  
Environmental Programs  
Los Alamos National Laboratory

Sincerely,



David R. Gregory, Project Director  
Environmental Operations  
Los Alamos Site Office

SS/DG/DK:sm

Cy: (w/enc.)

Laurie King, EPA Region 6, Dallas, TX  
Steve Yanicak, NMED-OB, White Rock, NM  
Tom Skibitski, NMED-OB, Santa Fe, NM  
Bonita Eichorst, DOE-LASO (date-stamped letter emailed)  
Mat Johansen, DOE-LASO, MS A316  
Danny Katzman, EP-LWSP, MS M992  
Susan G. Stiger, ADEP, MS M991  
Carolyn A. Mangeng, ADEP, MS M991  
Paul R. Huber, EP-LWSP, MS M992  
Tina Behr-Andres, EP-LWSP, MS M992  
Public Reading Room, MS M992  
Alison M. Dorries, ERSS-DO, MS M992  
Peggy Reneau, EP-ERSS, MS M992  
EP-LWSP File, MS M992  
RPF, MS M707  
IRM-RMMSO, MS A150