			Los Alamos
ffective Date: 5/19/11	Next Review D	Date: 5/19/13	EST. 1943
Environmental Pro	ograms Directo Projects	orate	
	- ·		
Standard Operatin	a Procedure		
Standard Operatin	g Procedure		
Standard Operating	g Procedure G STORM W	ATER SAMPLE	S
Standard Operating	g Procedure	ATER SAMPLE	S
Standard Operating or PROCESSIN APPROVAL SIGNATURES: Author:	g Procedure G STORM W	ATER SAMPLE	S
Standard Operating or PROCESSIN APPROVAL SIGNATURES: Author: Alethea Banar	g Procedure G STORM W	ATER SAMPLES	Date 05-17-2 oli
Standard Operating or PROCESSIN APPROVAL SIGNATURES: Author: Alethea Banar Responsible Line Manager	g Procedure G STORM W	ATER SAMPLES	S Date 05-17-2011 Date
Standard Operating or PROCESSIN APPROVAL SIGNATURES: Author: Alethea Banar Responsible Line Manager Steve Veenis	g Procedure G STORM W Organization ET-ER Organization PMFS-DO	ATER SAMPLES	S Date 05-17-2011 Date 5-18-11

Title: Processing Storm Water Samples	No.: SOP-5215	Page 2 of 10
	Revision: 2.1	Effective Date: 5/19/11

# 1.0 PURPOSE AND SCOPE

This procedure describes the process for filtering and preserving storm water samples for shipment to an analytical laboratory. This SOP applies to all LANL personnel and any subcontractors who conduct chemical preservation of water samples either in the field at the time of sample collection or in the Storm Water Processing Facility.

# 2.0 BACKGROUND AND PRECAUTIONS

#### 2.1 Background

The Environmental Protection Agency (EPA) issued National Pollution Discharge Elimination System (NPDES) Individual Permit requires LANL to monitor storm water runoff from Solid Waste Management Units (SWMUs) and Areas of Concern (AOCs), collectively referred to as Sites with regard to potential pollutants. The EPA issued NPDES Multi-Sector General Permit requires LANL to monitor storm water discharges and comply with requirements for storm water discharges associated with industrial activities.

Water samples are collected in the field. Chemical preservation and filtration are conducted in the field immediately following sample collection or in the Storm Water Processing Facility. If chemical preservation and filtration are conducted in the Storm Water Processing Facility, samples and contact waste shall be returned from the field in accordance with the applicable sampling procedure.

A LANL Project Leader will be appointed as the primary person with responsibility for the steps in this procedure.

### 2.2 Precautions

This procedure is used with an approved Integrated Work Document (IWD) and/or other safety documents as required. Use of acids and bases requires an IWD. Review IWDs for facility specific requirements, training, precautions and access controls.

### 3.0 EQUIPMENT AND TOOLS

- Copy of this procedure
- Copy of Integrated Work Document (IWD)
- Necessary keys
- Safety glasses with side shields
- Leather gloves or equivalent work gloves
- Glass and poly bottles appropriate for samples to be collected at the site (reference sampling plan)
- Lids for bottles
- Teflon tubing for intake
- Tygon tubing for exhaust

Title: Processing Storm Water Samples	No.: SOP-5215	Page 3 of 10
	Revision: 2.1	Effective Date: 5/19/11

# 4.0 STEP-BY-STEP PROCESS DESCRIPTION

4.1 Accep	ting Samples from the Field
Field Personnel	<ol> <li>Deliver to the Storm Water Processing Facility:         <ul> <li>Samples</li> <li>Completed, reviewed, and signed (relinquished by) Form 10013-1, ISCO Sampler Inspection and Sample Retrieval form (reference SOP-10013).</li> <li>Contact waste</li> </ul> </li> </ol>
Sample Processor	<ol> <li>Verify volumes, review, and accept samples by signing "Received by" on Form 10013-1. Maintain original with water samples.</li> </ol>
	<ol> <li>Provide a spreadsheet of all samples received to the Sample Data Manager with dates, times, and volumes of samples collected.</li> </ol>
4.2 Determ	nine Analyses Needed
Sample Data Manager	1. Generate Form 5215-1, Storm Water Sample Processing Log with labels (Attachment 1) using the appropriate LANL Sample Management Office application.
	2. Submit the forms and labels to Sample Processor.
Sample Processor	3. Generate Form 5215-2, Storm Water Sample Processing Form (Attachment 2) and append it with the above forms to the original Form 10013-1 and keep with water sample.
	4. Add Sample ID from Form 5215-1 to Form 5215-2 and 10013-1.
-	5. Add Field WO Number and SMA Number or Station Number for MSGP samplers from Form 5215-1 to Form 5215-2
4.3 Proce	ss Storm Water Samples
Sample Processor	<sup>1.</sup> Process only one sample (i.e., samples from one site) at a time.
	<b>Note:</b> Sample collection bottles are the bottles the sample was collected in the field. Sample containers are containers/bottles that the original sample is transferred to after processing. These containers are transferred to the Sample Management Office for shipment to the analytical laboratory.
-	<ol> <li>Don fresh gloves, lab coat, and protective eyewear. Long pants are required. No open toed shoes are allowed. Confirm eyewash is operational prior to processing samples.</li> </ol>
-	<ol> <li>Record the analytical sample requested for each sample bottle on Form 5215-2 Storm Water Sample Processing Form. If any blank rows are left, put a line through them and initial and date.</li> </ol>

Title: Processing Storm Water Samples	No.: SOP-5215	Page 4 of 10
	Revision: 2.1	Effective Date: 5/19/11

Sample Processor (cont.)	Affix appropriate label to sample container.		
	5. Split up samples into appropriate sample containers.		
4.4 Proc	essing Filtered Samples (if required)		
Sample Processor	<ol> <li>Filter samples IF REQUESTED on Form 5215-1, Storm Water Sample Processing Log. If not requested proceed to section 4.5.</li> </ol>		
	2. Using a suitable length of tubing, run a tube from the sample collection bottle to a filter and then addition tubing through the Geopump and into a new sample container. (This places the filter upstream of the Geopump, preventing the tubing from over-pressuring and blowing the filter off the tubing. This will make a mess.)		
	3. Turn on the Geopump.		
	4. If flow diminishes to less than about one mL per second during the filtering of a sample, replace the filter as follows:		
	<ul> <li>Hold the filter up and remove the tube from the sample collection bottle. Continue pumping until flow stops.</li> </ul>		
	Turn off Geopump.		
	Purge all water from the spent filter.		
	Remove the spent filter from tubing.		
	<ul> <li>Don new gloves (to prevent cross-contamination of tubing) and place fresh filter into tubing.</li> </ul>		
	Continue filtering process.		
	5. After the last sample bottle is filled, clean up the area.		
	6. Don new gloves before filtering a new sample (to prevent cross-contamination).		
4.5 Pres	erve Samples (applies to both filtered and unfiltered samples)		
Sample Processor	<ol> <li>IMPORTANT: Preservation entails the addition of acid or base to a sample. Acids used include hydrochloric acid (HCI), nitric acid (HNO<sub>3</sub>), and sulfuric acid (H<sub>2</sub>SO<sub>4</sub>). Bases used in preservation include sodium hydroxide (NaOH). These are all strong acids and bases that</li> </ol>		

- can cause severe burns. Extreme care should be taken when using these acids and bases that Refer to EP-ERSS-SOP-5056, Sample Containers and Preservation, for additional guidance.
  - 2. Preserve (add acid or base) samples according to the requirements on the sample container label and Form 5215-1 Storm Water Sample Processing Log.

Title: Processing Storm Water Samples	No.: SOP-5215	Page 5 of 10
	Revision: 2.1	Effective Date: 5/19/11

Sample3.After a minimum of 5 minutes, agitate preserved sample and then check pH. (pH for<br/>samples preserved with acid is expected to be less than 2. pH for samples preserved with<br/>base is expected to be greater than 12.)

Using a dropper, decant off a small volume of sample and test the pH and record as follows.

lf	Then
pH is less than 2	enter "pH<2" on the <i>Analytical Request Form/Chain of Custody</i> form
pH is greater than 12	enter "pH>12" on the <i>Analytical Request Form/Chain of Custody</i> form
pH is between 2 and 12	enter the pH value on the <i>Analytical Request Form/Chain</i> of Custody form (example: "pH=5")

- 4. Securely affix lid to sample container. Clean and dry the exterior of sample container, ensure lid is on securely, and check sample container for leakage and breakage.
- 5. Apply chain-of-custody tape to the lid/bottle.
- 6. Carefully place sample containers in the cooler and package sample containers with blue ice.
- Complete the Form 5215-1 Storm Water Sample Processing Log and Form 5215-2 Storm Water Sample Processing Form.

#### 4.6 Submit Samples for Shipping

Sample1.Submit samples with original 5215-1 Storm Water Sample Processing Log to the SampleProcessorManagement Office (WES-SMO) for shipping to the analytical laboratory in accordance with<br/>EP-ERSS-SOP-5057 Handling, Packaging, and Transporting Field Samples.

The SMO accepts samples by signing the Form 5215-1 Storm Water Sample Processing Log.

Retain a copy of Form 5215-1.

# 4.7 Clean Up Sample Processor 1. After each sample in the Storm Water Processing Facility is processed, clean the area.

Title: Processing Storm Water Samples	No.: SOP-5215	Page 6 of 10
---------------------------------------	---------------	--------------

#### 4.8 Waste Disposal

1.

#### Sample Processor

Place used empty glass bottles in cardboard box, close the box with tape, and dispose of box in the dumpster. Carefully place any broken glass in the Broken Glass Box in the Storm Water Processing Facility.

- 2. Seal contact waste in an appropriate sized baggie. Label with Site ID and date. Store in a satellite accumulation area prior to off-site disposal.
- 3. Pour excess waste water in an appropriate sized waste water container based on a Hazardous/Non-Hazardous listing. Label container with Site ID and date and store in a satellite accumulation area prior to off-site disposal.
- 4. If sample or contact waste is suspected to be contaminated with listed hazardous waste, store in a satellite accumulation area or a <90 day storage area for analysis prior to off-site disposal.

#### 4.9 Submit Records Package

Sample1.Submit the copy of Form 5215-1 with the original Forms 5215-2 and 10013-1and any otherProcessorpertinent documentation to the Process Control Coordinator.

#### 5.0 **RESULTING RECORDS**

- 1. Submit the following documents generated from this procedure to the Records Processing Facility in accordance with EP-DIR-SOP-4004, Records Transmittal and Retrieval Process.
  - Form 5215-1 Storm Water Sample Processing Log
  - Form 5215-2 Storm Water Sample Processing Form

#### 6.0 **DEFINITIONS**

None.

#### 7.0 PROCESS FLOW CHART

None.

### 8.0 ATTACHMENTS

Attachment 1: Form 5215-1 Example of Storm Water Sample Processing Log

Attachment 2: Form 5215-2 Storm Water Sample Processing Form

Title: Processing Storm Water Samples	No.: SOP-5215	Page 7 of 10
	Revision: 2.1	Effective Date: 5/19/11

# 9.0 **REVISION HISTORY**

Revision No. [Enter current revision number, beginning with Rev.0]	Effective Date [DCC inserts effective date for revision]	Description of Changes [List specific changes made since the previous revision]	Type of Change [Technical (T) or Editorial (E)]
0	1/06	New document issued as ENV-WQH-SOP-066.0, "Filtering and Chemical Preservation of Water Samples."	Т
0	3/9/2010	New document superseding and cancelling ENV-WQH- SOP-066.0. New process owner is ADEP; procedure issued as SOP-5215, "Processing Storm Water Samples".	т
1	July 2010	Minor edits and mention of MSGP storm water program.	E
2	3/18/2011	Minor edits; updated organization facility.	E
2.1	5/19/11	Minor edit; Updated reference to Form 10013-1 (Section 4.1, 4.2 and 4.9).	E

Effective Date: 5/19/11

#### **ATTACHMENT 1**

SOP-5215-1

Storm Water Sample Processing Log



Los Alamos National Laboratory

SMO 2

# STORM WATER SAMPLE PROCESSING LOG

FIELD WO #: ES-4315	SAMPLER No:	Los Alamos above Rio Grande	SMA No: E109.9
SAMPLER TYPE: DC	FIELD QC TYPE:	NA	SAMPLE MATRIX: WM
LOCATION TYPE: WCS	SAMPLE USAGE:	ENVSUR	
EVENT ID: 2749	EVENT NAME: ESR Snowmelt Sampling 2010		ling 2010
COLLECTION DATE/TIME: 5/24/2010 9:15:00 AM		RETRIEVAL DATE/TIME: 5/24/2010 9:15:00 AM	

#### SAMPLE PROCESSING REQUEST

SAMPLE ID: WTESR-10-15729		SAMPLE PREP: UF				
PRIORITY	ORDER		# of CONT.	PRESERVATIVE	SPECIAL	PROCESSING
	AMENDMENT		0	None		COMMENTO
	AMENDMENT		0	None		
0	SW-SSC	1 LITER POLY	1	ke		
1	SW-Hardness	0.5 LITER POLY	1	Nitric Acid		
1	SW-Metals-Total	0.5 LITER POLY	1	Nitric ud	1	
2	SW-D/F-1613B	1 LITER AMBER GLASS	2	100		
2	SW-PCB- 1668A-MDL	1 LITER AMBER GLASS	2	2		
3	SW-AM241	1 LITER POLY		Nit Aciu		
3	SW-Gamma	1 LITER POLY	1	Nuccid		
3	SW-Gross Alpha	1 LITER POLY		Vitric Acid		
3	SW-ISOPU	1 LITER POL		Nitric Acid		
3	SW-ISOU	1 LITER POL	1	Nitric Acid		
3	SW-SR90	1LILERT-C-	1	Nitric Acid		
SAMPLE COMMENTS:						

PROCESSED BY	Date/Time	REVIEWED BY	Date/Time
(Printed Name)		(Printed Name)	
(Signature)		(Signature)	
RELINQUISHED BY	Date/Time	RECEIVED BY	Date/Time
(Printed Name)		(Printed Name)	
(Signature)		(Signature)	
RELINQUISHED BY	Date/Time	RECEIVED BY	Date/Time
(Printed Name)		(Printed Name)	
(Signature)		(Signature)	

# **ATTACHMENT 1 (cont.)**

#### SOP-5215-1 (cont.)

# Storm Water Sample Processing Log New Label Format



Los Alamos National Laboratory			
Container: 0.5 LITER, POLY	Date: 5/24/2010		
WTESR-10-15726 1 of 1			
Analysis: SW-Metals-Dissolved	Time: 9:15 AM		

Los Alamos National Laboratory			
Container: 1 LITER, POLY	Date: 5/24/2010		
WTESR-10-15729 1 of 1			
Analysis: SW-Gross Alpha	Time: 9:15 AM		

Los Alamos National Laboratory

Preservative: Nitric Acid

Los Alamos National Laboratory			
Container: 1 LITER, POLY	Date: 5/24/2010		
WTESR-10-15729 1 of 1			
Analysis: SW-AM241	Time: 9:15 AM		

Container:	0.5 LITER, POLY		Date: 5/24/2010
WTESR-10	-15729	1 of 1	
			Time:

Preservative: Nitric Acid

Analysis: SW-Hardn

Preservative: Nitric Acid



Los Alamos National Laboratory

1 of 1

Date: 5/24/2010

Time:

9:15 AM

Analysis: SW-Hardn	9:15 AM
Preservativ Nitric Acid	
Los Alamos National Lab	oratory
Cont. ver: 1 LITER, POLY	Date: 5/24/2010
(TEL.R-10-15729 1 of 1	
	Time:

9:15 AM

Analysis: SW-ISOPU Preservative: Nitric Acid

Los Alamos National Laboratory			
Container: 1 LITER, POLY	Date: 5/24/2010		
WTESR-10-15729 1 of 1			
Analysis: SW-ISOU	Time: 9:15 AM		

Preservative: Nitric Acid

Los Alamos National Laboratory			
Container: 0.5 LITER, POLY	Date: 5/24/2010		
WTESR-10-15729 1 of 1			
Analysis: SW-Metals-Total	Time: 9:15 AM		

Preservative: Nitric Acid

Analysis: SW-Gamma

WTESR-10-15729

Container: 1 LITER, POLY

Effective Date: 5/19/11

Form 5215-2

# **ATTACHMENT 2**

#### SOP-5215-2

#### Storm Water Sample Processing Form



#### SOP5215

#### Storm Water Sample Processing Form

Field WO No. from Form 5215-1:

SMA No. from Form 5215-1:

Processing Personnel:

Date/Time Sample Processed:

Sample ID from Form 5215-1:

Field sample container number(s) used for aliquot sent to analytical laboratory

ISCO Bottle #	Analytical Sample (Poly Bottles)	ISCO Bottle #	Analytical Sample (Glass Bottles)
1		1	· · · · ·
2		2	
3		3	
4		4	
5		5	
6		6	
7		7	
8		8	
9		9	
10		10	
11		11	
12		12	
13		13	
14		14	
15		15	
16		16	
17		17	
18		18	
19		19	
20		20	
21		21	
22		22	
23		23	
24		24	
Single Stage Bo	ttle Type: Analytical S	Sample:	

Note: Samples collected in ISCO samplers are collected sequentially (1-21 or 1-24). Aliquots transferred to other containers for shipment to analytical laboratory(s) will be transferred in this sequential order only. Preferably, a single sample bottle will be used for a single analytical bottle.

Note: "Topping off" of sample bottles to be shipped to analytical laboratory(s) with any remaining field sample is NOT allowed.