

## Waste & Environmental Services

# **Standard Operating Procedure**

# for ROUTINE VALIDATION OF METALS ANALYTICAL DATA

#### APPROVAL SIGNATURES:

Subject Matter Expert:	Organization	Signature	Date
Bill Hardesty	WES-EDA	Signature on file	4/21/08
Quality Assurance Specialist:	Organization	Signature	Date
Laura Ortega	QA-IQ	Signature on file	5/14/08
Responsible Line Manager:	Organization	Signature	Date
Craig Eberhart	WES-EDA	Signature on file	4/21/08

Title: Routine Validation of Metals Analytical Data	No.: SOP-5165	Page 2 of 13
	Revision: 0	

#### 1.0 PURPOSE AND SCOPE

This procedure represents the minimum standards for evaluating routine Metals analytical data. This procedure is a mandatory document and shall be implemented by all Los Alamos National Laboratory (LANL or Laboratory) personnel and contractors who evaluate routine Metals analytical data for the specific LANL projects.

#### 2.0 BACKGROUND AND PRECAUTIONS

#### 2.1 Background

This procedure conforms to the requirements of Environmental Protection Agency (EPA) Methodologies and the EPA document, "U.S. EPA Contract Laboratory Program National Functional Guidelines for Inorganic Data Review." LANL data validation is performed according to procedures based upon the NNSA Model Data Validation Procedure. Data qualifiers and reason codes are assigned according to the specifications in this method specific procedure.

#### 2.2 Precautions

Nothing in this procedure precludes the data validator from going beyond the minimum requirements specified within this procedure. If additional directions are required, the data validator shall reference NNSA Model Data Validation Procedure, EPA method specific guidelines and/or National Functional Guidelines for Inorganic Data Review. Implementation of this procedure may be followed by a more focused and data use-specific evaluation of the data by the project chemist, especially if the implementation of this procedure indicates the data may contain technical deficiencies.

#### 3.0 EQUIPMENT AND TOOLS

None.

#### 4.0 STEP-BY-STEP PROCESS DESCRIPTION

4.1 Qualif	ications fo	or Data Validators
Data	1.	Possess a minimum of a bachelor's degree in chemistry, or one of the physical sciences
Validator		AND
		either two (2) years of experience in generating analytical data in an environmental analytical laboratory
		AND
		two (2) years of data validation experience.
	2.	Complete Attachment 1, Data Validation Cover Sheet, and Attachment 2, Metals Analytical Data Validation Checklist, during data validation.
	3.	Refer to Attachment 3, Guidance for the Qualifier and Reason Code Application, for additional guidance.

Title: Routine Validation of Metals Analytical Data	No.: SOP-5165	Page 3 of 13
	Revision: 0	

#### 4.2 Records

Data1.Submit the following records generated by this procedure to the Records ProcessingValidatorFacility:

- Completed Data Validation Cover Sheets; and
  - Completed Metals Analytical Data Validation Checklists.

#### 5.0 PROCESS FLOW CHART

For specific validation criteria follow the NNSA Model for Data Validation.

•

#### 6.0 ATTACHMENTS

Attachment 1 5165-1 Data Validation Cover Sheet (1 page)

Attachment 2 5165-2 Metals Analytical Data Validation Checklist (4 pages)

Attachment 3 5165-3 Guidance for the Qualifier and Reason Code Application (4 pages)

#### 7.0 REVISION HISTORY

Author: Bill Hardesty

Revision No. [Enter current revision number, beginning with Rev.0]	Effective Date [DCC inserts effective date for revision]	Description of Changes [List specific changes made since the previous revision]	Type of Change [Technical (T) or Editorial (E)]
0		New Document	Т

Title: Routine Validation of Metals Analytical Data	No.: SOP-5165	Page 4 of 13
	Revision: 0	

ATTACHMENT 1: EXAMPLE OF A DATA VALIDATION COVER SHEET

516	5-1						Records Use only
Example of a Data Validation Cover Sheet						• Los Alamos	
							EST.1943
				Section I.			
REQU	EST N		: VALIDATION D/	AT <u>E:</u>		I	_AB CODE:
CONT	RACTI	LABOR	ATORY NAME:				
VALID	ATOR:		ORGANIZATIO	DN:			
ANAL	YTICAL	SUITE	(CHECK ALL THAT APPLY):				
ו 🗆	PH-GR	80			XIN FUR	RANS	LCMSMS PERCHLORATES
י 🗆	PH-DR	0	METALS	🗌 РСВ	CONG	ENERS	—
	GENER	AL CHE	MISTRY 🗌 RADIOCHEMISTRY			GH	PESTICIDES/POLYCHLORINATED BIPHENYLS
	OTHER	(DESC	RIBE):				
	-	·	·				
			Section II.	Complete	ness Ch	neck	
YES	NO	N/A	(CHECK ONE)	YES	NO	N/A	(CHECK ONE)
			1. CHAIN-OF-CUSTODY FORM(S)				6. RAW/BSS DATA
			2. CASE NARRATIVE				7. QUALITY CONTROL FORMS
			3. SAMPLE RESULT FORMS				8. QUANTITATION REPORTS
			4. SAMPLE CHROMATOGRAMS				9. TICS FORMS
			5. STANDARD CHROMATOGRAMS				10. TICS MASS SPECTRA
	Comments/problems noted (include information about requests for further information submitted to the contract laboratory and agreed-upon date of resolution and contract laboratory point of contact):						
VALID	VALIDATOR'S SIGNATURE: DATE:						
SOP-5	SOP-5165, Revision 0.0 LOS ALAMOS Environmental Restoration Project						
	ATTACHMENT 2: METALS ANALYTICAL DATA VALIDATION CHECKLIST						
							CONTROLLED DOCUMENT

Users are responsible for ensuring they work to the latest approved revision. Printed or electronically transmitted copies are uncontrolled.

Title: Routine Validation of Metals Analytical Data	No.: SOP-5165	Page 5 of 13
	Revision: 0	

### 5165-2

## Metals Analytical Data Validation Checklist



Yes	No	N/A			Assign Qualifier Listed Below Criterion = Yes	
(Ch	ieck O	ne)			Non-detected Analyte	Detected Analyte
			1.	The holding time was >1 and ≤2 times the applicable holding time requirement.	UJ, 19	J-, 19
			2.	The holding time was >2 times the applicable holding time requirement.	R, 19a	J-, I9a
			3.	The instrument performance sample did not pass method acceptance criteria.	R, I16	R, I16
			4.	The mass calibration is not within 0.1 amu or %RSD is >5% for any isotope (Be, Mg, Co, In, Pb).	UJ, I16a	J, I16a
			5.	Samples were analyzed outside specific method tune time criteria.	N/A	J, I16b
			6.	The required instrument performance sample information is missing. Contact the SMO or external laboratory for information.	R, I16c	R, I16c
			7.	The affected results were not analyzed with a valid 5-point calibration curve and/or a standard at the reporting limit.	UJ, R, 17	J, 17
			8.	The affected analytes were analyzed with an initial calibration curve that exceeded the %RSD criteria and/or the associated multipoint calibration correlation coefficient is <0.995.	UJ, I7a	J+, I7a
			9.	The initial Calibration Verification (ICV) and/or Continuing Calibration Verification (CCV) were recovered outside the method-specific limits.	UJ, 17c	J, I7c
			10	. The ICV and/or CCV were not analyzed at the appropriate method frequency.	UJ, 17d	J+, I7d
			11	. Required calibration information is missing or samples were analyzed on an expired calibration. Contact the SMO or external laboratory for information.	R, I7f	R, I7f

Title: Routine Validation of Metals Analytical Data	No.: SOP-5165	Page 6 of 13
	Revision: 0	

Yes	No	N/A		Assign Qualifier Listed Below Criterion = Yes	
(Ch	eck O	ne)		Non-detected Analyte	Detected Analyte
			12. Metals interference check sample percent recover value is <50%.	R, I2	J-, I2
			13. Metals interference check sample percent recovery value is ≥50% and <80%	UJ, I2a	J-, I2a
			<ol> <li>Metals interference check sample percent recovery value is &gt;120%.</li> </ol>	N/A	J+, l2b
			15. Metals interference check sample was not analyzed with the samples.	R, I2c	R, I2c
			16. The sample result is ≤5X the concentration of the related analyte in the method blank.	N/A	U, 14
			17. The affected analytes are considered estimated and biased high because this analyte was identified in the method blank but was >5X.	N/A	J+, I4a
			18. The sample result is ≤5X the concentration of the related analyte in the instrument blank and continuing calibration blank.	N/A	U, 14b
			19. Continuing calibration blanks were not analyzed at the appropriate method frequency.	UJ, I4c	J, I4c
			20. The sample result is ≤5X the concentration of the related analyte in the trip blank, rinsate blank, or equipment blank.	N/A	U, 14d
			21. Required method blank information is missing. Data may not be acceptable for use. Contact the SMO or external laboratory for information.	R, I4e	R, I4e
			22. The associated matrix spike recovery was <a>&lt;10%. Follow the external laboratory limits</a> located within the associated data package.	R, 16	R, 16
			23. The associated matrix spike recovery was <the LAL but &gt;10%. Follow the external laboratory limits located within the associated data package.</the 	UJ, 16a	J-, I6a
			24. The associated matrix spike recovery was > the UAL. Follow the external laboratory limits located within the associated data package.	UJ, 16b	J+, l6b

Title: Routine Validation of Metals Analytical Data	No.: SOP-5165	Page 7 of 13
	Revision: 0	

Yes	No	N/A		Assign Qualifier Criterio	
(Check One)		ne)		Non-detected Analyte	Detected Analyte
			25. Required matrix spike information is missing. Data may not be acceptable for use. Contact the SMO or external laboratory for information. If the LCS information is present, do not Reject. Qualify data based on the LCS information.	R, l6c	R, l6c
			26. The sample and the duplicate sample results were ≥5X the RL and the duplicate RPD was >20% for water samples and >35% for soil samples.	UJ, I10a	J, I10a
			27. The duplicate sample was not prepared and/or analyzed with the samples for unspecified reasons. The duplicate information is missing. Data may not be acceptable for use. Contact the SMO or external laboratory for information.	UJ, l10d	J, l10d
			28. The LCS percent recovery was <10%. Follow the external laboratory limits located within the associated data package.	R, I12	R, I12
			29. The LCS percent recover was < the LAL but >10%. Follow the external laboratory limits located within the associated data package.	UJ, I12a	J-, I12a
			30. The LCS percent recovery was > the UAL. Follow the external laboratory limits located within the associated data package.	N/A	J+, l12b
			31. The LCS documentation is missing. Data may not be acceptable for use. Contact the SMO or external laboratory for information. Do not Reject if MS/MSD information is present. Qualify according to MS/MSD criteria.	R, I12c	R, I12c
			32. The quantitating IS area count is <10% for metals window in relation to the initial calibration blank. Follow the method-specific windows.	R, I1a	J, I1a
			33. The IS area count for the quantitating IS is <60% but >10% for metals window in relation to the initial calibration blank. Follow the method- specific windows.	UJ, I1b	J, I1b

Title: Routine Validation of Metals Analytical Data	No.: SOP-5165	Page 8 of 13
	Revision: 0	

Yes	No	N/A		-	r Listed Below If on = Yes
(Check One)				Non-detected Analyte	Detected Analyte
			<ul><li>34. The IS area count for the quantitating IS is</li><li>&gt;125% in relation to the metals initial calibration blank. Follow method-specific windows.</li></ul>	UJ, 11c	J, I1c
			35. Required IS information is missing. Data may not be acceptable for use. Contact the SMO or external laboratory for information.	R, I1d	R, I1d
			36. Serial dilution sample %D was >10% and the sample result was >50X the MDL (>100X the MDL for ICPMS). Qualify ONLY the sample used for the serial dilution.	UJ, I18	J, I18
			37. Serial dilution sample was not analyzed with the samples.	UJ, I18a	J, I18a
			38. The sample result was reported as detected between the IDL and the EDL.	N/A	J, I1
			39. Duplicate, dilution, or reanalysis.	UJ, 188	J, 188
			40. Qualification of data via data validation did not occur based on Quality Control requirements in this procedure. Adhere to the external laboratory qualifiers found within the Form I analytical data summary sheets generated by the external laboratory.	U, U_LAB	J, J_LAB, NQ, NQ
			41. The LANL project chemist identified quality deficiencies in the reported data that require further qualification. This code can ONLY be used and/or under advisement by the LANL project chemist.	UJ, R, I19	J, R, I19



No.	Valid Flag Code Nondetect	Valid Flag Code Detect	Valid Reason Code	Valid Reason Description	
1	N/A	J	l1	The sample result was reported as detected between the IDL and the EDL.	
2	UJ	J	l10a	The sample and the duplicate sample results were ≥5X the RL and the duplicate RPD was >20% for water samples and >35% for soil samples.	
3	UJ	J	l10d	The duplicate sample was not prepared and/or analyzed with the samples for unspecified reasons. The duplicate information is missing. Data may not be acceptable for use. Contact the SMO or external laboratory for information.	
4	R	R	112	The LCS percent recovery was <10%. Follow the external laboratory limits located within the associated data package.	
5	UJ	J-	l12a	The LCS percent recovery was < the Lower Acceptance Limit (LAL) but >10%. Follow the external laboratory limits located within the associated data package.	
6	N/A	+L	l12b	The LCS percent recovery was > Upper Acceptance Limit (UAL). Follow the external laboratory limits located within the associated data package.	
7	R	R	l12c	The LCS documentation is missing. Data may not be acceptable for use. Contact the SMO or external laboratory for information. Do not Reject if MS/MSD information is present. Qualify according to MS/MSD criteria.	
8	R	R	116	The instrument performance sample did not pass the method acceptance criteria.	

No.	Valid Flag Code Nondetect	Valid Flag Code Detect	Valid Reason Code	Valid Reason Description	
9	UJ	J	l16a	The mass calibration is not within 0.1 amu or %RSD exceeds 5% for any isotope (Be, Mg, Co, In, Pb).	
10	N/A	J	l16b	Samples were analyzed outside specific method tune time criteria.	
11	R	R	l16c	The required instrument performance sample information is missing. Contact the SMO or external laboratory for information.	
12	UJ	J	118	Serial dilution sample RPD was >10% and the sample results was >50X the MDL (>100X the MDL for ICPMS). Qualify ONLY the sample used for the serial dilution.	
13	UJ	J	l18a	Serial dilution sample was not analyzed with the samples.	
14	UJ, R	J, R	119	The project chemist identified quality deficiencies in the reported data that requires further qualification. This code can ONLY be used and/or under the advisement by the project chemist.	
15	R	J	l1a	The quantitating IS area could is <10% for metals window in relation to the initial calibration blank. Follow method-specific windows.	
16	UJ	J	l1b	The IS area count for the quantitating IS is <60% but >10% for metals window in relation to the initial calibration blank. Follow method-specific windows.	
17	UJ	J	l1c	The IS area count for the quantitiating IS is >125% in relation to the metals initial calibration blank. Follow method-specific windows.	
18	R	R	l1d	Required IS information is missing. Data may not be acceptable for use. Contact the SMO or external laboratory for information.	
19	R	J-	12	Metals interference check sample percent recovery value is <50%.	
20	UJ	J-	l2a	Metals interference check sample percent recovery value is ≥50% and <80%.	
21	N/A	J+	l2b	Metals interference check sample percent recovery value is >120%.	
22	R	R	l2c	Metals interference check sample was not analyzed with the samples.	

No.: SOP-5165 Page 11 of 13 Revision: 0

No.	Valid Flag Code Nondetect	Valid Flag Code Detect	Valid Reason Code	Valid Reason Description	
23	N/A	U	14	The sample result is ≤5X the concentration of the related analyte in the method blank, which indicates the reported detection is considered indistinguishable from contamination in the blank.	
24	N/A	J	l4a	The affected analytes are considered estimated and biased high because this analyte was identified in the method blank but was >5X.	
25	N/A	U	l4b	The sample result is ≤5X the concentration of the related analyte in the ICB/CCB, which indicates the reported detection is considered indistinguishable from contamination in the blank.	
26	UJ	J	l4c	Continuing calibration blanks were not analyzed at the appropriate method frequency.	
27	N/A	U	l4d	The sample result is ≤5X the concentration of the related analyte in the trip blank, equipment blank, or rinsate, which indicates the reported detection is considered indistinguishable from contamination in the blank.	
28	R	R	l4e	Required method blank information is missing. Data may not be acceptable for use. Contact the SMO or external laboratory for information.	
29	R	R	16	The associated matrix spike recovery was <10%. Follow the external laboratory limits located within the associated data package.	
30	UJ	J-	l6a	The associated matrix spike recovery was < the LAL but >10%. Follow the external laboratory limits located within the associated data package.	
31	UJ	J+	l6b	The associated matrix spike recovery was > the UAL. Follow the external laboratory limits located within the associated data package.	
32	R	R	l6c	Required matrix spike information is missing. Data may not be acceptable for use. Contact the SMO or external laboratory for information.	
33	UJ, R	J	17	The affected results were not analyzed with a valid 5-point calibration curve and/or a standard at the reporting limit.	

Title:	Routine	Validation	of Metals	<b>Analytical Data</b>
--------	---------	------------	-----------	------------------------

No.	Valid Flag Code Nondetect	Valid Flag Code Detect	Valid Reason Code	Valid Reason Description	
34	UJ	J	I7a	The affected analytes were analyzed with a initial calibration curve that exceeded the %RSD criteria and/or the associated multipoint calibration correlation coefficient is <0.995.	
35	UJ	J	l7c	The ICV and/or CCV were recovered outside the method-specific limits.	
36	UJ	J	l7d	The ICV and/or CCV were not analyzed at the appropriate method frequency.	
37	R	R	l7f	Required calibration information is missing or samples were analyzed on an expired calibration. Contact the SMO or external laboratory for information.	
38	UJ	J	188	Duplicate, dilution, or reanalysis.	
39	UJ	J-	19	The extraction/analytical holding time are exceeded by <2X the published method for holding times.	
40	R	J-	19a	The extraction/analytical holding time are exceeded by >2X the published method for holding times.	
41	U	J, NQ	U_LAB, J_LAB, NQ	Qualification of the data via data validation did not occur because of Quality Control requirements in this procedure. Adhere to external laboratory qualifiers found within the Form I analytical data summary sheets generated by the external laboratory.	

Title: Routine Validation of LC/MS/MS	No.: SOP-5165	Page 13 of 13
	Revision: 0	

This page left blank intentional.