

SUSANA MARTINEZ Governor

JOHN A. SANCHEZ Lieutenant Governor

NEW MEXICO ENVIRONMENT DEPARTMENT

Hazardous Waste Bureau

2905 Rodeo Park Drive East, Building 1 Santa Fe, New Mexico 87505-6303 Phone (505) 476-6000 Fax (505) 476-6030 www.nmenv.state.nm.us



DAVE MARTIN Secretary

BUTCH TONGATE Deputy Secretary

JAMES H. DAVIS, Ph.D. Director Resource Protection Division

EP2012-5286

CERTIFIED MAIL - RETURN RECEIPT REQUESTED

November 29, 2012

Peter Maggiore Assistant Manager, Env. Projects Office Los Alamos Site Office, DOE 3747 West Jemez Rd, MS A316 Los Alamos, NM 87544 Jeffrey D. Mousseau, Associate Director Environmental Programs Los Alamos National Security, L.L.C. P.O. Box 1663, MS M991 Los Alamos, NM 87545

RE: APPROVAL WITH MODIFICATIONS DRILLING WORK PLAN FOR REGIONAL AQUIFER WELL R-47 LOS ALAMOS NATIONAL LABORATORY EPA ID#NM0890010515 HWB-LANL-MISC-GW

Dear Messrs Maggiore and Mousseau:

The New Mexico Environment Department (NMED) is in receipt of the United States Department of Energy (DOE) and the Los Alamos National Security, L.L.C.'s (collectively, the Permittees) document entitled *Drilling Work Plan for Regional Aquifer Well R-47* (Plan) dated November 8, 2012 and referenced by EP2012-0254.

NMED has reviewed the Permittees' Plan, and hereby issues this approval with the following modifications.

1. The Permittees must make a valid attempt to collect representative groundwater samples at the first occurrence of perched saturation. Groundwater samples shall be collected using a portable pump (e.g., submersible piston pump) placed in the borehole soon after groundwater is encountered. Samples shall be submitted for explosive compounds, volatile organic compounds, trace metals, and major-ion chemistry (e.g., nitrate as nitrogen). Messrs. Maggiore and Mousseau November 29, 2012 Page 2

- 2. When backfilling the well above the screened interval with sealant, the Permittees must take care not to allow bentonite sealant to migrate downward into the screened interval, such as what may have occurred at well R-64. This may warrant the placement of the fine-grained sand collar above the top of regional saturation.
- 3. The Permittees must take a more aggressive effort at developing well R-47 than for previously installed regional-aquifer wells. This approach may require additional swabbing and/or jetting followed by the removal of water in excess of the normal amount pumped from a newly installed regional well which usually equates to the estimated amount of drill-water injected into the regional aquifer.
- 4. The final location for R-47 must be selected subject to NMED consultation and approval.

Should you have any questions, please contact Michael Dale of my staff at (505) 661-2673.

Sincerely, John E. Kieling Chief Hazardous Waste Bureau

cc:

D. Cobrain, NMED HWB
N. Dhawan, NMED HWB
B. Wear, NMED HWB
J. Kulis, NMED HWB
J. Kulis, NMED HWB
M. Dale, NMED HWB
T. Skibitski, NMED DOE OB
J. Schoeppner, NMED GWQB
S. Yanicak, NMED DOE OB, MS M894
L. King, EPA 6PD-N
S. Rydeen, San Ildefonso Pueblo
J. Chavarria, Santa Clara Pueblo
J. McCann, EP-CAP, MS M992
C. Rodriquez, DOE-LASO, MS A316
H. Shen, DOE-LASO, MS A316
W. Woodworth, DOE-LASO, MS A316

File: Reading and LANL 2012, Drilling Work Plan for Regional Aquifer Well R-47

New Mexico Environment Department Hazardous Waste Bureau 2905 Rodeo Park Drive East, Bldg.1 Santa Fe, New Mexico 87505

03-12-12 P12:34 RCVD





s.3.

DATE

016H26523547 \$05.750 11/30/2012 Mailed From 87505

US POSTAGE

Hasler

NAME Elain Rice z# 113017 DATE 12.3.12

Jeffrey D. Mousseau, Associate Director Environmental Programs Los Alamos National Security, L.L.C. P.O. Box 1663, MS-991 MS-A150 Los Alamos, New Mexi co 87545

Haldadalahalahall

J1300188